

Hook up silicone wire AGR 硅橡胶高温安装电子线



Description:

tinned stranded copper conductor ;  
 Rated temperature: 180°C, rated voltage: 300/500 volts  
 Insulation of wires to ensure easy  
 Stripping and cutting.  
 Resistant to acids, alkalis, oil , moisture and fungi.

说明:

导体使用镀锡绞铜线  
 额定温度: 180°C 额定电压: 300V/500V  
 绝缘, 优良热稳定性和机械耐磨  
 易开线和剥皮。  
 抗酸碱, 耐油及防潮霉性能好.

Application:

For general purpose internal wiring of electronic  
 and electrical equipment

应用:

一般商用电热电器及设备仪器内部  
 连接线. 变压器及电机引出线。

Specification: 技术参数:

STYLE	Conductor size (No./ mm) ±0.005mm	Insulation Thickness (mm)	Overall diameter (mm)	Conductor Dia. (mm)	Conductor resistance 20°C (Ω/Km)
AGR-0.2	12/0.15	0.50	1.60	0.20	95.0
AGR-0.3	16/0.15	0.50	1.70	0.30	71.2
AGR-0.4	23/0.15	0.50	1.85	0.40	49.6
AGR-0.5	20/0.18	0.60	2.15	0.50	40.1
AGR-0.75	30/0.18	0.60	2.35	0.75	26.7
AGR-1.0	32/0.20	0.70	2.70	1.00	20.0
AGR-1.5	30/0.25	0.70	3.00	1.50	13.7
AGR-2.0	41/0.254	0.70	3.30	2.00	11.1
AGR-2.5	49/0.25	0.80	3.60	2.50	8.21
AGR-4.0	56/0.30	0.80	4.20	4.00	5.09
AGR-6.0	84/0.30	1.00	5.20	6.00	3.39
AGR-10.0	84/0.40	1.00	6.30	10.00	1.95

Order reference: 订货资料: shenzhen QiFuRui electronics company.

Colors available: white, red, yellow, green, blue, brown, black, yellow/green

可选颜色: 白色, 红色, 绿色, 橙色, 紫色, 黄色, 绿色, 蓝色, 棕色, 黑色, 黄绿.

Delivery : 交货日期: 15 days after accepting purchase orders. 接到订单后 15